

WHAT IS CLAIMED IS:

1. A surround surveillance system mounted on a mobile body for surveying surroundings around the mobile body, comprising an omniazimuth visual system, the omniazimuth visual system including:

at least one omniazimuth visual sensor including an optical system capable of obtaining an image with an omniazimuth view field area therearound and capable of central projection transformation of the image into an optical image, and an imaging section including an imaging lens for converting the optical image obtained by the optical system into image data;

an image processor for transforming the image data into at least one of panoramic image data and perspective image data;

a display section for displaying one of a panoramic image corresponding to the panoramic image data and a perspective image corresponding to the perspective image data; and

a display control section for controlling the display section,

wherein the optical system includes a hyperboloidal mirror which has a shape of one sheet of

09975678-101101

a two-sheeted hyperboloid, an optical axis of the hyperboloidal mirror being identical with an optical axis of the imaging lens, and the principal point of the imaging lens being located at one of focal points of the hyperboloidal mirror, and

the display section displays the perspective image transformed from the bird's-eye image of the mobile body and surroundings thereof.

2. A surround surveillance system according to claim 1, wherein the at least one omniazimuth visual sensor is located such that a bird's-eye image of the mobile body and surroundings thereof is transformed into the image data.

3. A surround surveillance system according to claim 1, wherein the display section simultaneously or selectively displays the panoramic image and the perspective image.

4. A surround surveillance system according to claim 1, wherein the display section displays an image seen in a direction opposite to a most likely moving direction of the mobile body.

09975678-101401

5. A surround surveillance system according to claim 1, wherein the image processor transforms image data corresponding to a first area within the omniazimuth view field area around the optical system into first perspective image data.

6. A surround surveillance system according to claim 5, wherein in response to control by the display control section, the image processor transforms image data corresponding to a second area within the omniazimuth view field area around the optical system which does not overlap with the first area into a second perspective image data which does not coincide with the first perspective image data.

7. A surround surveillance system according to claim 6, wherein the second area is identical to an area which is obtained by performing at least one of translational transfer processing and zoom-in/zoom-out processing on the first area.

8. A surround surveillance system according to claim 1, wherein the optical system is positioned such that an optical axis of the optical system is perpendicular to

09075678-101101

a most likely moving direction of the mobile body.

9. A surround surveillance system according to claim 1, wherein in response to control by the display control section, the display section displays an image showing the mobile body on a display screen of the display section such that the mobile body is shown at a predetermined position on a displayed image on the display screen.

10. A surround surveillance system according to claim 1, wherein the display section simultaneously displays an image seen in a direction opposite to a most likely moving direction of the mobile body and an image seen in a direction which is not identical or opposite to the most likely moving direction of the mobile body.

11. A surround surveillance system according to claim 1, wherein the mobile body is a vehicle.

12. A surround surveillance system according to claim 11, wherein:

the vehicle includes a first bumper provided at a most likely moving direction side of the vehicle and

09975678-101101
TOTOT 82952660

a second bumper provided at a side of or the vehicle opposite to the most likely moving direction side; and

the at least one omniazimuth visual sensor includes a first omniazimuth visual sensor placed on the first bumper and a second omniazimuth visual sensor placed on the second bumper.

13. A surround surveillance system according to claim 12, wherein:

the first omniazimuth visual sensor is placed on one of a right end and a left end of the first bumper with respect to the most likely moving direction of the vehicle; and

the second omniazimuth visual sensor is placed on one end of the second bumper which is diagonal to the end of the first bumper where the first omniazimuth visual sensor is placed with respect to a body of the vehicle.

14. A surround surveillance system according to claim 13, wherein the display section displays an image obtained by combining a first perspective image derived from the first omniazimuth visual sensor and a second perspective image derived from the second omniazimuth visual sensor.

09975678.101101

15. A surround surveillance system according to claim 1, wherein:

the image processor includes a storage section for storing mobile body image data;

the image processor combines the mobile body image data from the storage section with the perspective image data derived from the optical system; and

the display section displays based on the combined image data a perspective image including the image showing the mobile body.

16. A surround surveillance system according to claim 15, wherein the mobile body image data is image data created by using computer graphics software.

17. A surround surveillance system according to claim 15, wherein the mobile body image data is image data obtained by capturing an image of the mobile body.

18. A surround surveillance system according to claim 1, wherein:

the omniazimuth visual system further includes a temperature measurement section for measuring an environmental temperature of the mobile body;

00975678-101101

when the environmental temperature measured by the temperature measurement section is equal to or lower than a predetermined temperature, the display section displays the perspective bird's-eye image of the mobile body and surroundings thereof after the mobile body becomes movable.

19. A surround surveillance system according to claim 13, wherein, when the display section displays a perspective image of an overlapping region between a display region of a perspective bird's-eye image of the mobile body and surroundings thereof which is obtained through the first omniazimuth visual sensor and a display region of a perspective bird's-eye image of the mobile body and surroundings thereof which is obtained through the second omniazimuth visual sensor, the display section displays based on control by the display control section a perspective image derived from one of the first omniazimuth visual sensor and the second omniazimuth visual sensor.

09975678-101101